

BOAT SERIES

R410A
REFRIGERANT



ASB-05A
ASB-09A
ASB-12A
ASB-16A
ASB-24A

- Compact space-saving design
- Power supply 50/60 Hz
- High COP compared to air-cooled units
- Corrosion proof and rust prevention coating
- High quality of heat insulating material
- Operating temperature range:
Cooling: 16~43 °C (10 °C~35 °C of inlet water)
Heating: -10~30 °C (4 °C~25 °C of inlet water)
- Wired and remote controller as standard

FIX SPEED



ASB-12A



ASB-24A



TECHNICAL PARAMETERS



MODEL			ASB-05A	ASB-09A	ASB-12A
Capacity cooling / heating	kW		1,1 / 1,4	2,1 / 2,2	3,1 / 3,2
Power supply	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-		1,96 / 2,64	2,33 / 2,50	2,82 / 2,91
Sound pressure level at 1m	ID	dB(A)	58	58	58
Dimension (w x h x d)/Net weight	ID	mm/kg	285 x 408 x 295 / 25,5	380 x 408 x 310 / 28,0	380 x 420 x 330 / 33,0
Operating temperature range cooling / heating	°C		16-43 / -10-30	16-43 / -10-30	16-43 / -10-30

MODEL			ASB-16A	ASB-24A	
Capacity cooling / heating	kW		3,2 / 4,0	6,40 / 6,65	
Power supply	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER / SCOP	-		2,67 / 3,08	4,41 / 3,80	
Sound pressure level at 1m	ID	dB(A)	62	60	
Dimension (w x h x d)/Net weight	ID	mm/kg	450 x 465 x 330 / 37,5	595 x 529 x 386 / 60,5	
Operating temperature range cooling / heating	°C		16-43 / -10-30	16-43 / -10-30	

For detailed technical parameters see technical part of catalogue. This catalogue sheet does not apply to project documentation.
Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.