

# MOBILE DEHUMIDIFIERS

R290  
NATURAL  
REFRIGERANT



CFO-16P  
CFO-20P  
CFO-40P

- Powerful dehumidifying function
- Silent operation and mode indicators
- Drying
- Low power consumption
- Autorestart
- Indication of opened water tank
- External drain water outlet
- Protection of overflowing
- 2-year warranty



CFO-16P



CFO-20P

CFO-40P



## TECHNICAL PARAMETERS



MODEL		CFO-16P	CFO-20P	CFO-40P
Dehumidifying volume	l/den	16,0	20,0	40,0
Power supply	Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Power input / Max. power input	-	220 / 245	360 / 450	670 / 900
Rated current	-	1,1	2,1	4,0
Sound pressure level at 1m	dB(A)	41 / 38	43 / 41 / 39	48 / 45 / 42
Water tank volume	l	2,5	3,5	6,5
Optimal room size	m <sup>2</sup>	20	28	48
Dimension (w x h x d)/Net weight	mm/kg	305 x 490 x 192 / 10,5	363 x 577 x 245 / 15,5	396 x 625 x 286 / 22,5
Operating temperature range	°C	5 ~ 32	5 ~ 32	5 ~ 32

R290 (100% CH<sub>3</sub>CH<sub>2</sub>CH<sub>3</sub>)

The values stated in the sheet are complying with norm EN810

Dehumidifying volume is measured according to EN60335-2-40, test conditions: DB 30%, RH 80%

Hermetically sealed system.

GWP of the refrigerant used: 3.