

WINDOW SERIES

ECOLOGICAL
REFRIGERANT  R32

ASW-09BI ASW-12BI

- Energy class A
- Cooling mode only
- Dirty filter alarm
- Low voltage startup
- Automatic restart function
- Remote controller



MANUAL CONTROL PANEL

- Possibility to control unit via buttons on front panel of air conditioner.



DC INVERTER

TECHNICAL PARAMETERS



MODEL			ASW-09BI	ASW-12BI	
Cooling capacity	kW		2,7	3,7	
Power supply	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER	-		3,45	3,54	
Energy class cooling	-		A	A	
Sound pressure level at 1m	interior	dB(A)	50 / 48/ 46	50 / 48/ 46	
	exterior	dB(A)	56 / 54/ 52	58 / 56/ 54	
Dimension (w x h x d)/Net weight	mm/kg		560 x 375 x 710 / 43,0	660 x 428 x 700 / 50,0	
Operating temperature range cooling	°C		16 ~ 43	16 ~ 43	

For detailed technical parameters see technical part of catalogue. This catalogue sheet does not apply to project documentation.
 Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R32 (single component refrigerant HFC), GWP of refrigerant used: 675.
 Hermetically sealed system.