

TOWER SERIES




R410A
REFRIGERANT



AST-24AI

- Designed with an emphasis on aesthetics
- Usable for larger areas such as offices, meeting rooms, restaurants etc.
- Turbo heating and cooling
- Equipped with horizontal and vertical electric louver
- Self-diagnosis function
- Intelligent defrost system
- WiFi control
- Controlled by built-in panel or remote controller
- Remote controller



DC INVERTER

TECHNICAL PARAMETERS

MODEL			AST-24AI	
Capacity cooling / heating	kW		7,2 / 7,5	
Power supply	Hz / V		1~ / 50 / 220-240	
SEER / SCOP	-		6,1 / 4,0	
Energy class cooling/heating (av.)	-		A++ / A+	
Sound pressure level at 1m	ID	dB(A)	49 / 45 / 42 / 39	
	OD	dB(A)	60	
Dimension (w x h x d)/Net weight	ID	mm/kg	507 x 1770 x 320 / 40,0	
	OD	mm/kg	955 x 700 x 396 / 53,5	
Operating temperature range cooling/heating	°C		-15 ~ 48 / -15 ~ 24	

For detailed technical parameters see technical part of catalogue. This catalogue sheet does not apply to project documentation.
 Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.